
## Slimline Autofill Countertop 10L with Built-in Filtration




	<b>.</b>			
Water	Roil	er	Feati	ires

- Compact 215mm width
- Replaceable water filter provides better tasting beverages and reduces limescale build-up
- Desired water temperature can be easily set between 98°C down to 70°C for more delicate speciality teas
- Will dispense up to 206 cups per hour / 31 litres, with 13 litre rapid draw-off
- The boilers eco-mode can be programmed to suit the location, reducing running costs and saving energy
- Robust chrome tap, can be switched between controllable and constant flow with 220mm tap height above tray
- Tough plastic drip tray, easy to empty and clean, with drain outlet for optional waste water connection

## Dimensions (mm)





Customer Services Telephone: +44 (0)344 879 3588

Product Code	070029
Model no.	SAF10CT
EAN Barcode	5011139070029
Product type	SL Autofill Boiler
Warranty Period	2 years parts and labour

Technical Information				
Product Info:				
Filtered	Yes			
Capacity (litres)	10			
Packed Dimensions W x D x H (mm)	310 x 540 x 70			
Drip Tray Dimensions W x D x H (mm)	210 x 195 x 51			
Product Weight (kg)	11			
Packed Weight (kg)	14			
Colour	Bright Annealed Stainless Steel & Black			
Body Construction / Material	430 Stainless Steel			
Tank Construction / Material	304 grade Stainless Steel			
Trim and drip tray plastic type	PC ABS			
Tap Material type	Chrome			
Dual Function Tap	Yes			
Safety Standards test	EN60335			
Nonslip Feet	Yes			
Boil Dry cut-out	Yes			
Performance:				
Heat up Time to 98°c (minutes)	34			
Rapid Draw off—Litres	13			
Rapid Draw off—Pints	228			
Rapid Draw off—Cups	36			
Output per Hr—Litres	31			
Output per Hr—Pints	55			
Output per Hr—Cups	206			
Recovery Per min—Litres	0.45			
Recovery Per min—Pints	0.88			
Recovery Per min—Cups	3			
Heat up time 70°c—98°c (minutes)	8			
Cool down time 98°c—70°c (minutes)	322			
Standard power consumption (kW/hr)	0.12			
Installation:				
Hard wiring required	No			
UK fitted plug	Yes			
Cable length (m)	1.5			
Water feed pipe length (m)	2			
Max. water inlet pressure (bar)	8			
Element power rating	2.8			
Phase type	Single			
Nominal voltage	230V 50-60Hz			
Electrical supply current (A)	13			
Water inlet connection fitting	3/4" BSP			

Email: customer.services@glendimplex.com

Website: www.burco.co.uk



