Slimline Autofill Countertop 10L (Pushbutton) with Built-in Filtration


Product Code	070050
Model no.	SAF10PB
EAN Barcode	5011139070050
Product type	SL Autofill Boiler
Warranty Period	2 years parts and labour



Water Boiler Features

- Compact 215mm width
- Replaceable water filter provides better tasting beverages and reduces limescale build-up
- Desired water temperature can be easily set between 98°C down to 70°C for more delicate speciality teas
- Will dispense up to 206 cups per hour / 31 litres, with 13 litre rapid draw-off
- The boilers eco-mode can be programmed to suit the location, reducing running costs and saving energy
- Responsive delivery system water flow ceases when button is released
- Tough plastic drip tray, easy to empty and clean, with drain outlet for optional waste water connection

Dimensions (mm)



Customer Services Telephone: +44 (0)344 879 3588

Product Info:	
Filtered	Yes
Capacity (litres)	10
Packed Dimensions W x D x H (mm)	310 x 540 x 710
Drip Tray Dimensions W x D x H (mm)	210 x 195 x 53
Product Weight (kg)	11
Packed Weight (kg)	14
Colour	Bright Annealed Stainless Steel & Black
Body Construction / Material	430 Stainless Steel
Tank Construction / Material	304 grade Stainless Steel
Trim and drip tray plastic type	PC ABS
Tap Material type	N/A
Dual Function Tap	N/A
Safety Standards test	EN60335
Nonslip Feet	Yes
Boil Dry cut-out	Yes
Performance:	
Heat up Time to 98°c (minutes)	34
Rapid Draw off—Litres	13
Rapid Draw off—Pints	22.8
Rapid Draw off—Cups	86
Output per Hr—Litres	31
Output per Hr—Pints	55
Output per Hr—Cups	206
Recovery Per min—Litres	0.45

Technical Information

UK fitted plug	Yes
Cable length (m)	1.5
Water feed pipe length (m)	2
Max. water inlet pressure (bar)	8
Element power rating	2.8
Phase type	Single
Nominal voltage	230V 50-60Hz
Electrical supply current (A)	13

Email: customer.services@glendimplex.com Website: www.burco.co.uk





Recovery Per min-Pints

Recovery Per min—Cups
Heat up time 70°c—98°c (minutes)

Water inlet connection fitting

Installation:
Hard wiring required

Cool down time 98°c-70°c (minutes)

Standard power consumption (kW/hr)

0.88

8

322

0.12

No

3/4" BSP