



Heatingcable NUCS18W/m



With the lightweight and 4mm NUCS heating cables, you can rest assured that our products are eco-friendly and easy to install.

The 4 mm cable is developed for modern, low-build floors. We recommend our NTB-2R thermostat for user friendly operation either stand alone or together with Nobø Energy Control system.

NUCS heating cables carry a 15-year warranty.

We recommend the following effects for Nobø NUCS heating cable: - Bedroom: 60-80W/m² - Livingroom: 80-100W/m² - Bathroom: 130-150W/m²


Nobø NUCS heatingcable is attached to a cable reel that makes it easy to install and shape for any concrete floor installation. The series resistive heating cable has a PVC sheath and a generous 3m cold connection end for simple and flexible connection to any thermostat.

Cables are recommended for floor heating in standard concrete floors and low-build floors. The heating cable can be attached to a reinforced net or glued directly on a non-flammable surface. Always use proper insulation before installing the heating cable for the most energy-efficient heating system. Underfloor heating products must be installed by an approved installer.



Malli	Sähkönumero	Teho (W)	EAN	Vastus (Ω)	Paino (kg)	Pituus (m)
NUCS18W-160W-8,5m	8130020	160	8590875063184	312,6-326	0,85	8,5
NUCS18W-260W-14,5m	8130021	260	8590875063191	193,1-223,6	0,9	14,5
NUCS18W-320W-18,5m	8130022	320	8590875063207	157,5-182,3	1	18,5
NUCS18W-420W-24,0m	8130023	420	8590875063214	119,2-138	1,15	24
NUCS18W-520W-28,4m	8130024	520	8590875063221	96,6-111,8	1,25	28,4
NUCS18W-600W-34,4m	8130025	600	8590875063238	97,2-83,9	1,5	34,4
NUCS18W-680W-37,9m	8130026	680	8590875063245	73,8-85,4	1,6	37,9
NUCS18W-830W-46,1m	8130027	830	8590875063252	60,4-69,9	1,95	46,1
NUCS18W-1000W-57,5m	8130028	1000	8590875063269	50,8-58,9	2,35	57,5
NUCS18W-1200W-68,9m	8130029	1200	8590875063276	41,8-48,5	3	68,9
NUCS18W-1500W-83,2m	8130030	1500	8590875063283	33,1-38,3	3,4	83,2
NUCS18W-1700W-100,4m	8130031	1700	8590875063290	29,5-34,2	4,25	100,4
NUCS18W-2200W-122,7m	8130032	2200	8590875063306	22,8-26,4	5,25	122,7
NUCS18W-2600W-147,6m	8130033	2600	8590875063313	19,2-22,3	6,85	147,6

Technical data: Nobø NUCS18W/m Heatingcable

Cable Construction	Doble cord solid resistance wires	
Insulation	Flourpolymer 0,3mm thickness	
Protectionscreen	7 tinned copperwires Ø 0,3mm + AIPET foil	
Jacket	PVC therm resistant (105°C) - 0,8mm thickness	
Cable diameter	4mm - 3m long black cold end	
Permanent heating endurance:	-30 +80 (Temp. during installation -5°C)	
Max powerload	18W/m	
Operating voltage	230V	
Covering	IP67	
Class of mechanical endurance:	M1 Classification	
Minimum radius	30mm	
Self extinguishing	Yes	
Jacket colour	Red	

Underfloor Heating Thermostat NTB-2R



Malli	Valm. tuoten:o	Sähkönumero	GTIN	Mitat ilman pakkausta (mm)	Pakkauksen mitat (mm)	Paino, sis pakk.
Nobø NTB 2R	86000101	5422485	7030690104224	86x86x43	90x90x55	200g