

A



Dimensions



Key Features

- Instant water heating at point of use, no stored water heat losses or wasted energy
- Compact design ideal for wall mounting under or adjacent to basin mounting in all four orientations
- 6kW high efficiency bare wire heating elements for rapid response heating and improved resistance to scaling
- No controls - hot tap activated at 2 litres per minute flow
- Fully temperature stabilised with thermal cut-out safety protection
- Pre-wired with 700mm length of 4mm² double insulated 3 core cable ready for connection
- Suitable for use with water resistivity >1300Ωcm
- M22/M24 quarter turn spray head basin taps are recommended for optimum performance
- A Energy efficiency rated with a 1 year UK guarantee

Technical Details

Model	RIWH6
EAN /Bar Code No.	5011139067395
Power Output (kW)	6
Current Rating (Amps) @240V	27
Water Resistivity	>1300Ωcm
Thermal Cut-out Protection	80°C
Energy Rating (Class)	A
Energy Rating (%)	39
Consumption (kWh/A)	458
Load Profile	XS
Sound (dB)	15
Operating Pressure (bar)	1 - 7.5
Minimum Flow Rate (l/min)	2
Water Connections	½" BSP
IP Rating	IPX4
Box Dimensions (mm)	205 x 215 x 115
Gross Weight (kg)	1.8
Net Weight (kg)	1.56
Pallet Quantity	216
Approvals / Mark	BEAB & CE
UK Guarantee (years)	1

Product Range

Item Code:	Model No:	Description	kW
45673201	RIWH6	Inline Instant Water Heater	6

