MS6 MINI STORED WATER HEATER

Dimensions





Key Features

- · Compact 6 litre capacity unit, ideal for single outlets
- 1.5kW heating element for rapid heat up and recovery
- · Thermostatic control up to 65°C with thermal cut-out safety protection
- · Heating element `ON' neon indicator
- Rustproof, glass-lined tank for long-life and higher energy efficiency
- Magnesium sacrificial anode additional anti-corrosion tank protection
- High density thermal CFC-free polyurethane insulation to minimise heat loss
- 1/2"BSP male inlet and outlet connections
- 1-metre fitted cable and UK Plug
- Include an accompanying 6bar pressure relief valve and dielectric junctions which prevent an electrolytic reaction occurring to safeguard against potential aggressive corrosion
- Supplied with wall mounting bracket and fixing bolt pack
- B Energy efficiency rated with 1 year UK guarantee

Product Range				
Item Code:	Model No:	Description	kW	
47789701	MS6	Mini Stored Water Heater 6 Litre	1.5	

Accessories			
Item Code:	Model No:	Description	
87783101	CWP	Cold Water Control Pack	
87783103	TBV	Thermostatic Blending Valve	
97783236	TUN	$\frac{1}{2}$ " male to $\frac{3}{4}$ " female angled Tundish	






TBV



TUN



DEPTH: 255mm

ModelMS6EAN /Bar Code No.5017084479719Storage Capacity (Litres)6Power Output (kW)1.5Current Rating (Amps) @240V6.5Thermostatic Control (°C)0Thermal Cut-out ProtectionReplacementEnergy Rating (Class)0Daily Consumption Qelec (kWh)2.73Daily Consumption Qelec (kWh)1.5Sound (dB)15Sound (dB)1.7Min. Unrestricted 15mm Pipewok1.7 metreWater Connections%"BSP (via Dielectric Junctions)IP Rating1.10 x 300 x 320Gross Weight (kg)3.10 x 330 x 320Net Weight (kg)4.7Pallet QuantitySEAB & CEUK Guarantee (years)1	Technical Details				
Storage Capacity (Litres)6Power Output (kW)1.5Current Rating (Amps) @240V6.5Thermostatic Control (°C)5 to 65Thermal Cut-out ProtectionReplacementEnergy Rating (Class)0Daily Consumption Qelec (kWh)2.73Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)IP Rating1.7 metreWater Connections12°BSP (via Dielectric Junctions)IP Rating310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)54Approvals / MarkBEAB & CE	Model	MS6			
Power Output (kW)1.5Current Rating (Amps) @240V6.5Chermostatic Control (°C)5 to 65Thermostatic Control (°C)S to 65Thermal Cut-out ProtectionReplacementEnergy Rating (Class)BEnergy Rating (%)32.5Daily Consumption Qelec (kWh)2.73Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)Water Connections'2"BSP (via Dielectric Junctions)IP Rating117 metreBox Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)54Approvals / MarkBEAB & CE	EAN /Bar Code No.	5017084479719			
Current Rating (Amps) @240V6.5Current Rating (Amps) @240V6.5Thermostatic Control (°C)5 to 65Thermal Cut-out ProtectionReplacementEnergy Rating (Class)BEnergy Rating (%)32.5Daily Consumption Qelec (kWh)2.73Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections'4"BSP (via Dielectric Junctions)IP Rating19X4Gross Weight (kg)5.8Net Weight (kg)5.4Pallet Quantity54Approvals / MarkBEAB & CE	Storage Capacity (Litres)	6			
Thermostatic Control (°C)5 to 65Thermal Cut-out ProtectionReplacementEnergy Rating (Class)BEnergy Rating (%)32.5Daily Consumption Qelec (kWh)2.73Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections½"BSP (via Dielectric Junctions)IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)54Approvals / MarkBEAB & CE	Power Output (kW)	1.5			
Thermal Cut-out ProtectionReplacementEnergy Rating (Class)BEnergy Rating (%)32.5Daily Consumption Qelec (kWh)2.73Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections's"BSP (via Dielectric Junctions)IP Rating19X4Gross Weight (kg)5.8Net Weight (kg)5.4Approvals / MarkBEAB & CE	Current Rating (Amps) @240V	6.5			
Energy Rating (Class)BEnergy Rating (%)32.5Daily Consumption Qelec (kWh)2.73Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections½"BSP (via Dielectric Junctions)IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)54Approvals / MarkBEAB & CE	Thermostatic Control (°C)	5 to 65			
Energy Rating (%)32.5Daily Consumption Qelec (kWh)2.73Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections½"BSP (via Dielectric Junctions)IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)54Approvals / MarkBEAB & CE	Thermal Cut-out Protection	Replacement			
Daily Consumption Qelec (kWh)2.73Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections'\s"BSP (via Dielectric Junctions)IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)54Pallet Quantity54Approvals / MarkBEAB & CE	Energy Rating (Class)	В			
Load ProfileXXSSound (dB)15Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections½"BSP (via Dielectric Junctions)IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)54Pallet Quantity54Approvals / MarkBEAB & CE	Energy Rating (%)	32.5			
Sound (dB)15Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections½"BSP (via Dielectric Junctions)IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)54Pallet Quantity54Approvals / MarkBEAB & CE	Daily Consumption Qelec (kWh)	2.73			
Operating Pressure psi/(bar)87 (6)Min. Unrestricted 15mm Pipework1.7 metreWater Connections½"BSP (via Dielectric Junctions)IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)4.7Pallet Quantity54Approvals / MarkBEAB & CE	Load Profile	XXS			
Number of the second	Sound (dB)	15			
Water Connections½"BSP (via Dielectric Junctions)IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)4.7Pallet Quantity54Approvals / MarkBEAB & CE	Operating Pressure psi/(bar)	87 (6)			
IP RatingIPX4Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)4.7Pallet Quantity54Approvals / MarkBEAB & CE	Min. Unrestricted 15mm Pipework	1.7 metre			
Box Dimensions (mm)310 x 330 x 320Gross Weight (kg)5.8Net Weight (kg)4.7Pallet Quantity54Approvals / MarkBEAB & CE	Water Connections	1/2"BSP (via Dielectric Junctions)			
Gross Weight (kg) 5.8 Net Weight (kg) 4.7 Pallet Quantity 54 Approvals / Mark BEAB & CE	IP Rating	IPX4			
Net Weight (kg) 4.7 Pallet Quantity 54 Approvals / Mark BEAB & CE	Box Dimensions (mm)	310 x 330 x 320			
Pallet Quantity 54 Approvals / Mark BEAB & CE	Gross Weight (kg)	5.8			
Approvals / Mark BEAB & CE	Net Weight (kg)	4.7			
	Pallet Quantity	54			
UK Guarantee (years) 1	Approvals / Mark	BEAB & CE			
	UK Guarantee (years)	1			





CE

MS6 STORED WATER HEATER

JANUARY 2021