

# MW/EW Stored Water Heaters

Hot water on demand for up to four outlets from a central mains pressured water supply, with wall or floor mounting options.

## Key Features

- Superior insulation combined with short pipe runs minimises heat loss, saving energy
- Provides a balanced hot and cold water supply, via existing taps or mixers for convenience
- Hot water on demand for up to four hand basin outlets
- Adjustable thermostat up to 70°C, with safety cut-out protection
- Fitted magnesium sacrificial anode for tank protection
- Supplied with dielectric connectors, wall bracket and fixings for floor or wall mounting
- B Energy Rating
- 1 year UK manufacturer guarantee

MW - factory fitted temperature and pressure relief device



EW - accompanying 6bar expansion relief valve



Thermostatic Blending Valve



Cold Water Control Pack: expansion vessel, PRV, check valve



Tundish

**B**

## Product Dimensions

10L



360mm

Product depth: 254mm

15L



360mm

Product depth: 300mm

410mm

In small unvented water heaters the hot water expansion can often be accommodated back into the cold water mains supply, as indicated in the Water Regulations. Where this is not possible the installer will need to fit a set of cold water controls.

Catalogue Number	Model/Description
47789101	MW10 10Ltr 3kW water heater
47789201	MW15 15Ltr 3kW water heater
47789301	EW10 10Ltr 3kW water heater
47789401	EW15 15Ltr 3kW water heater
Accessories	
87783101	CWP Cold Water Control Pack
87783103	TBV Thermostatic Blending Valve
97783236	TUN Tundish 1/2" male 3/4" female

Technical Information	
Capacity	10 Litres & 15 Litres
Cable Connection	Rear bottom right entry
Power	3kW@240V
Water	Operating water pressure 1-12bar (15-174psi) (above 6bar a cold water pack is required) Inlet/outlet connections 15mm (1/2" BSP)
Approvals	BEAB & CE mark
Ingress Protection	IPX4

