



B

Dimensions



Key Features

- 10 and 15 litre capacity units with factory fitted temperature and pressure relief device
- 3kW heating element for rapid heat up and recovery
- Thermostatic control up to 65°C with thermal cut-out safety protection
- Heating element 'ON' neon indicator
- Rustproof, glass-lined tank for long-life and higher energy efficiency
- Magnesium sacrificial anode additional anti-corrosion tank protection
- High density thermal CFC-free polyurethane insulation to minimise heat loss
- Supplied with dielectric junctions which prevent an electrolytic reaction occurring to safeguard against potential aggressive corrosion
- Wall mounting bracket and bolt pack also included
- B Energy efficiency rated with 1 year UK guarantee

Product Range

Item Code:	Model No:	Description	kW
47789101	MW10	Stored Water Heater 10 Litre	3
47789201	MW15	Stored Water Heater 15 Litre	3

Accessories

Item Code:	Model No:	Description
87783101	CWP	Cold Water Control Pack
87783103	TBV	Thermostatic Blending Valve
97783236	TUN	½" male to ¾" female angled Tundish



CWP



TBV



TUN

Technical Details

Model	MW10	MW15
EAN /Bar Code No.	5017084479115	5017084479214
Storage Capacity (Litres)	10	15
Power Output (kW)	3	3
Current Rating (Amps) @240V	13	13
Thermostatic Control (°C)	5 to 60	5 to 60
Thermal Cut-out Protection	Manual Reset	Manual Reset
Energy Rating (Class)	B	B
Energy Rating (%)	32.7	32.8
Consumption (kWh/annum)	564	562
Load Profile	XXS	XXS
Sound (dB)	15	15
Operating Pressure psi/(bar)	87 (6)	87 (6)
Min. Unrestricted 15mm Pipework	2.8 metres	4.2 metres
Water Connections	½"BSP (via Dielectric Junctions)	
IP Rating	IPX4	IPX4
Box Dimensions (mm)	475 x 410 x 282	480 x 415 x 300
Gross Weight (kg)	8.13	9.2
Net Weight (kg)	8	9
Pallet Quantity	24	18
Approvals / Mark	BEAB & CE	BEAB & CE
UK Guarantee (years)	1	1

