



Selectronic Premier thermostatic showers offer the highest level of temperature accuracy. This control technology combined with the many enhanced user features make them the perfect choice for Care Sector specification as well for peace of mind showering safety in any family home.


Key Features

- Highly accurate, temperature control to $\pm 0.5^{\circ}\text{C}$ for a safe and comfortable showering experience
- Push button controls with audible adjustment confirmation for ease of operation
- Large LED digital temperature display
- Phased shutdown safety protection for next user cool start up and scale protection
- 3 maximum temperature limiter lock options (40°C), (41°C), (43°C) or unlocked ($25 - 46^{\circ}\text{C}$) set at installation
- Simple push button rapid commissioning
- Data logger for user and performance analysis
- Right hand side multi-entry connection options
- 5 spray mode shower head with easy rub-clean nozzles
- 540mm x 22mm stainless steel riser rail with 4-point fixing rail brackets
- 1.25 metre anti-kink flexible shower hose, adjustable handset clamp, soap dish and shower hose retaining ring

Product Range

Item Code:	Model No:	Description	kW
100054	RSELP85S	Selectronic Premier Standard	8.5
100061	RSELP95S	Selectronic Premier Standard	9.5
100078	RSELP108S	Selectronic Premier Standard	10.8

Dimensions



Technical Details

Model	RSELP85S	RSELP95S	RSELP108S
Item Code	100054	100061	100078
EAN /Bar Code No.	5011139100054	5011139100061	5011139100078
Output (kW)	8.5	9.5	10.8
Current Rating (Amps)	36	40	45
Energy Rating (Class)	A	A	A
Energy Rating (%)	37	37	37
Consumption (kWh/A)	495	488	489
Load Profile	XS	XS	XS
Sound (dB)	15	15	15
Running Pressure psi (bar)	10 (0.7) - 140 (10)		
Temp. Control Accuracy	$\pm 0.5^{\circ}\text{C}$		
Start-up Temperatures	40, 41 or 43°C		
Temperature Range	25 - 46°C		
IP Rating	IPX5		
Approvals / Mark	BEAB, BEAB CARE, WRAS, RNIB & CE		
UK Warranty (years)	5*		
Box dimensions (mm)	580 x 325 x 145		
Gross weight (kg)	4.5		
Net weight (kg)	3.8		
Full pallet quantity	60		
Showers per layer	6		



*Subject to product registration within 30 days.

