



3 LITRE



5 & 7.5 LITRE

Sensaboil wall mounted water boiling units for beverage making and food preparation in busy commercial environments. Available in a choice of capacities all have a 3kW heating element for rapid heat recovery and delivery of up to 206 cups per hour.

Key Features

- Convenient boiling water readily available at point of use, no filling and waiting for kettles to boil
- Available in 3, 5 and 7.5 litre capacity models to suit a range of user requirements
- Catering grade stainless steel tank for great tasting drinks
- Finished in stainless steel or durable white painted easy wipe clean finish
- 3kW heating element for rapid response re-heating with thermal cut-out safety protection
- Simple chrome tap operation, push and hold to control flow or pull and lock for a continuous dispense
- Touch on/off control panel with neon indication status and descale now notification
- Supplied with 3/4" BSP inlet connector/adaptor and 2 metres of blue cold water supply hose

Product Range

Item Code:	Model No:	Description	kW
22672801	SB3W	Sensaboil 3 Litre White	3
22673801	SB5W	Sensaboil 5 Litre White	3
22674801	SB7W	Sensaboil 7.5 Litre White	3
22672805	SB3S	Sensaboil 3 Litre S/Steel	3
22673805	SB5S	Sensaboil 5 Litre S/Steel	3
22674805	SB7S	Sensaboil 7.5 Litre S/Steel	3

Dimensions



DEPTH: 195mm
(All models)

Technical Details

White Painted Models	SB3W	SB5W	SB7W
EAN /Bar Code No. (W)	5017084222803	5017084223800	5017084224807
Stainless Steel Models	SB3S	SB35	SB7S
EAN /Bar Code No. (S)	5017084222858	5017084223855	5017084224852
Water Capacity (Litres)	3	5	7.5
Heating Element (kW)	3	3	3
Max. Water Temperature	98°C	98°C	98°C
Delivery up to (Cups/hr)	206	206	206
Initial Draw off (Cups)	20	34	51
Operating Pressure (bar)	1 to 8	1 to 8	1 to 8
Water Inlet Connection	3/4" BSP	3/4" BSP	3/4" BSP
Ambient Temperature	5 to 30°C	5 to 30°C	5 to 30°C
IP Rating	IPX4	IPX4	IPX4
Pack Dimensions (mm)	385 x 460 x 360	533 x 460 x 360	533 x 460 x 360
Packed Weight (kg)	7.7	9.6	9.6
Net Weight Empty (kg)	4.8	6.2	6.2
Weight Full (kg)	7.8	11.2	13.7
Approvals / Mark	CE	CE	CE
UK Guarantee (years)	2	2	2

